



CURVE

DISPONIBILE: CRUDO (CR)
 RICOTTO (RIC)
MATERIALE: AISI 304 - AISI 304L (J)
 AISI 316 - AISI 316L (K)
FINITURA: GREZZA (GR)
 LUCIDO EST/INT (LL)
 LUCIDO ESTERNO (LE)
DA TUBOELETTRONITO (EU)
DA LAMIERA ASTM 240 (LA)
CURVA A 90° (9)
CURVA A 45° (4)
CURVA A 180° (8)



ART. 1400 - CURVA 90° A SALDARE - SERIE GAS

| | | | | | | | | | | | | | |
|---|--------------------|-----------|------------|------------|------------|------------|--------------|--------------|------------|--------------|----------|--------------|-----------|
|  | DN(ISO) GAS-ASA | 8 1/4" | 10 3/8" | 15 1/2" | 20 3/4" | 25 1" | 32 1 1/4" | 40 1 1/2" | 50 2" | 65 2 1/2" | 80 3" | 90 3 1/2" | 100 4" |
| | D. EST | 13.7 | 17.2 | 21.3 | 26.9 | 33.7 | 42.4 | 48.3 | 60.3 | 76.1 | 88.9 | 101.6 | 114.3 |
| | RAGGIO | 20 | 28.5 | 31.8 | 28.5 | 38 | 47.6 | 57.1 | 76.1 | 96 | 114.3 | 133.5 | 152.5 |
| | SPESS. | 2 | 1 - 2 | 1.5 - 2 | 1.5 - 2 | 1.5 - 3 | 1.5 - 3 | 1.5 - 3 | 1.5 - 3 | 1.5 - 3 | 1.5 - 3 | 2 - 3 | 2 - 3 |
| DN (ISO) GAS-ASA | 125 5" | 150 6" | 200 8" | 250 10" | 300 12" | 350 14" | 400 16" | 450 18" | 500 20" | 600 24" | | | |
| D. EST | 139.7 | 168.3 | 219.1 | 273 | 323.9 | 355.6 | 406.4 | 457.2 | 508 | 609.6 | | | |
| RAGGIO | 190.5 | 228.5 | 305 | 381 | 457.2 | 533.4 | 609.6 | 685.8 | 762 | 914 | | | |
| SPESS. | 2 - 4 | 2 - 6 | 2 - 6 | 2 - 6 | 2.5 - 6 | 2.5 - 6 | 2.5 - 6 | 2.5 - 6 | 3 - 6 | 3 - 6 | | | |


ART. 1402 - CURVA 90° - MISURE DISPONIBILI A RICHIESTA

| | | | | | | | | | | | | | |
|---|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-------|--|--|
|  | D. EST | 20 | 25 | 30 | 43 | 50 | 53 | 80 | 83 | 84 | 204 | | |
| | RAGGIO | 30 | 37.5 | 45 | 64.5 | 75 | 75 | 120 | 124.5 | 126 | 270 | | |
| | SPESS. | 1.5 - 2 | 1.5 - 2 | 1.5 - 2 | 1.5 - 2 | 1.5 - 3 | 1.5 - 2 | 1.5 - 3 | 1.5 - 2 | 1.5 - 2 | 2 - 3 | | |
| | | | | | | | | | | | | | |

ART. 1404 - CURVA 90° DA TUBO EU ESTREMITA' A SALDARE - SERIE ALIMENTARE

| | | | | | | | | | | | | | |
|---|--------|-------|------|--------|--------|------|--------|------|-------|-----|-----|-----|-----|
|  | DIN | 10 | 15 | 20 | 25 | 32 | 40 | 50 | 65 | 80 | 100 | 125 | 150 |
| | D. EST | 12 | 18 | 22 | 28 | 34 | 40 | 52 | 70 | 85 | 104 | 129 | 154 |
| | RAGGIO | 26 | 35 | 40 | 43 | 52 | 60 | 72 | 85 | 93 | 110 | 187 | 225 |
| | SPESS. | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 2 | 2 | 2 | 2 |
| H | 26 | 35 | 40 | 50 | 55 | 60 | 72 | 85 | 95 | 110 | 187 | 225 | |
| SMS/BS | 1/2" | 3/4" | 1" | 1 1/4" | 1 1/2" | 2" | 2 1/2" | 3" | 4" | | | | |
| D. EST | 12.7 | 19.05 | 25.4 | 31.8 | 38.1 | 50.8 | 63.5 | 76.1 | 101.6 | | | | |
| RAGGIO | — | 29 | 38 | 48 | 56 | 72 | 84 | 85 | 110 | | | | |
| SPESS. | — | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 2 | 2 | | | | |
| H | — | 34 | 40 | 50 | 56 | 75 | 85 | 85 | 110 | | | | |

ART. 1406 - CURVA 90° DA TUBO EU ESTREMITA' A MANDRINARE - SERIE ALIMENTARE

| | | | | | | | | | | | | | |
|---|--------|-------|------|--------|--------|------|--------|------|-------|-----|-----|-----|-----|
|  | DIN | 10 | 15 | 20 | 25 | 32 | 40 | 50 | 65 | 80 | 100 | 125 | 150 |
| | D. EST | 12 | 18 | 22 | 28 | 34 | 40 | 52 | 70 | 85 | 104 | 129 | 154 |
| | RAGGIO | 26 | 35 | 40 | 43 | 52 | 60 | 72 | 85 | 93 | 110 | | |
| | SPESS. | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 2 | 2 | 2 | |
| A | 38 | 47 | 52 | 70 | 78 | 85 | 97 | 110 | 118 | 140 | | | |
| SMS/BS | 1/2" | 3/4" | 1" | 1 1/4" | 1 1/2" | 2" | 2 1/2" | 3" | 4" | | | | |
| D. EST | 12.7 | 19.05 | 25.4 | 31.8 | 38.1 | 50.8 | 63.5 | 76.1 | 101.6 | | | | |
| RAGGIO | — | 29 | 38 | 48 | 56 | 72 | 84 | 85 | 110 | | | | |
| SPESS. | — | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 2 | 2 | | | | |
| A | — | — | 75 | 80 | 90 | 100 | 115 | 130 | 150 | | | | |

SEGUE

CURVE

MATERIALE

GREZZA (GR)

DA TUBO ELETTROUNITO (EU)

A 90° (9)

AISI 304-AISI 304L (J) LUCIDA INT/EST (LL) DA LAMIERA ASTM 240 (LA)

A 45° (4)

AISI 316-AISI 316L (K) LUCIDA EST (LE)

A 180° (8)

ART. 1408 -
CURVE A 90° ESTREMITA' A MANDRINARE RM = 3D - ALIMENTARE

| | | | | | | | | | | | | | |
|--|-----------------|------------|------------|------------|------------|------------|------------|------------|----------|------------|----------|--|--|
| | SMS/BS D.EST | 1" 25.4 | 1¼ 31.8 | 1½ 38.1 | 40 | 2" 50.8 | 53 | 2½ 63.5 | 70 | 3" 76.2 | 104 | | |
| | RAGGIO | 75 | 93 | 115 | 120 | 150 | 150 | 185 | 210 | 215 | 200 | | |
| | SPESS. U | 1.5 115 | 1.5 136 | 1.5 140 | 1.5 170 | 1.5 225 | 1.5 225 | 1.5 240 | 2 240 | 2 250 | 2 250 | | |
| | | | | | | | | | | | | | |

ART. 1410 -
CURVE A 180° ESTREMITA' A SALDARE - ALIMENTARE

| | | | | | | | | | | | | | |
|--|----------------------|-------------------|--------------------|--------------------|--------------------|------------------|-------------------|------------------|----------------|----------------|-----------------|--|--|
| | DIN | 10 | 15 | 20 | 25 | 32 | 40 | 50 | 65 | 80 | 100 | | |
| | D.EST SPESS. L | 12 1.5 52 | 18 1.5 70 | 22 1.5 80 | 28 1.5 100 | 34 1.5 112 | 40 1.5 126 | 52 1.5 144 | 70 2 170 | 85 2 186 | 104 2 220 | | |
| | SMS-BS | 1" | 1½ | 2" | 2½ | 3" | 4" | | | | | | |
| | D.EST SPESS. L | 25.4 1.5 81 | 38.1 1.5 104 | 50.8 1.5 143 | 63.5 1.5 168 | 76.2 2 171 | 101.6 2 220 | | | | | | |

ART. 1412 -
CURVE A 180° ESTREMITA' A MANDRINARE - ALIMENTARE

| | | | | | | | | | | | | | |
|--|------------------|-----------------|------------------|-------------------|-------------------|------------------|------------------|------------------|-----------------|-----------------|-----------------|--|--|
| | DIN D.EST | 10 12 | 15 18 | 20 22 | 25 28 | 32 34 | 40 40 | 50 52 | 65 70 | 80 85 | 100 104 | | |
| | SPESS. L A | 1.5 52 38 | 1.5 70 47 | 1.5 80 52 | 1.5 100 70 | 1.5 112 78 | 1.5 126 85 | 1.5 144 97 | 2 170 110 | 2 186 118 | 2 220 140 | | |
| | SMS-BS D.EST | 1" | 1½ | 2" | 2½ | 3" | 4" | | | | | | |
| | SPESS. L A | 1.5 81 75 | 1.5 104 90 | 1.5 143 100 | 1.5 168 115 | 2 171 130 | 2 220 150 | | | | | | |

ART. 1414 -
CURVE A 45° ESTREMITA' A SALDARE - SERIE GAS

| | | | | | | | | | | | | | |
|--|----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------|-----------------|-------------------|------------|------------|------------|
| | DN - ISO GAS-ASA | 15 1/2" | 20 3/4" | 25 1" | 32 1¼ | 40 1½ | 50 2" | 65 2½ | 80 3" | 90 3½ | 100 4" | 125 5" | 150 6" |
| | D.EST SPESS. H | 21.3 1.5 - 2 18 | 26.9 1.5 - 2 20 | 33.7 1.5 - 2 27 | 42.4 1.5 - 2 33 | 48.3 1.5 - 2 40 | 60.3 1.5 - 2 52 | 76.1 2 60 | 88.9 2 80 | 101.6 2 108 | 114.3 2 | 139.7 2 | 168.3 2 |
| | | | | | | | | | | | | | |

ART. 1416 -
CURVE A 45° ESTREMITA' A MANDRINARE - ALIMENTARE

| | | | | | | | | | | | | | |
|--|------------------|-----------------|------------------|------------------|------------------|-----------------|-----------------|------------------|----------------|----------------|----------------|--|--|
| | DIN D.EST | 10 12 | 15 18 | 20 22 | 25 28 | 32 34 | 40 40 | 50 52 | 65 70 | 80 85 | 100 104 | | |
| | SPESS. M H | 1.5 15 45 | 1.5 20 60 | 1.5 20 65 | 1.5 24 73 | 1.5 27 83 | 1.5 27 89 | 1.5 30 103 | 2 30 108 | 2 30 120 | 2 35 151 | | |
| | SMS-BS D.EST | 1" | 1½ | 2" | 2½ | 3" | 4" | | | | | | |
| | SPESS. M H | 1.5 25 80 | 1.5 30 105 | 1.5 30 103 | 1.5 35 115 | 2 35 135 | 2 35 150 | | | | | | |