

## VALVOLE SANITARIE SERIE "ON-OFF"

CON ATTUATORE PNEUMATICO NORMALMENTE CHIUSO O NORMALMENTE APERTO

MATERIALE: AISI 304 - AISI 316

FINITURA: LUCIDO INTERNO

### ART. 880 - VERSIONE AD "L"

	sms	25	38	51	63	76	101	
	L	45	56	70	78	85	135	
	E	38	43,5	53	57	65,5	90,5	
	A	241	253	315	329	366	453	
	TC	28	34	40	52	70	85	101
	L	45	50	56	70	78	93	135
E	38	44	45	53	59,5	66	90,5	
A	243	252	256	315	334	372	453	



### ART. 882 - VERSIONE A "T"

	sms	25	38	51	63	76	101	
	L	45	56	70	78	85	135	
	E	38	43,5	53	57	65,5	90,5	
	A	241	253	315	329	366	453	

### ART. 884 - VERSIONE A "LL"

	DIN	25	38	51	63	76	101	
	L	45	56	70	78	85	135	
	E	54	67	80	96	103	171	
	A	295	320	395	425	469	624	

### ART. 886 - VERSIONE A "LT"

	sms	25	38	51	63	76	101	
	L	45	56	70	78	85	135	
	E	54	67	80	96	103	171	
	A	295	320	395	425	469	624	

### ART. 888 - VERSIONE A "TL"

	sms	25	38	51	63	76	101	
	L	45	56	70	78	85	135	
	E	54	67	80	96	103	171	
	A	295	320	395	425	469	624	

### ART. 890 - VERSIONE A "TT"

	sms	25	38	51	63	76	101	
	L	45	56	70	78	85	135	
	E	54	67	80	96	103	171	
	A	295	320	395	425	469	624	

### ART. 892 - VERSIONE AD "L"

	din	25	32	40	50	65	80	100
	L	58	61	60	73	81	89	152
	E	57	63	64	72	80,5	91	115
	A	262	271	275	334	355	397	478
	sms	25	38	51	63	76	101	
	L	58	60	73	81	89	160	
E	53	63,5	73	81	89,5	115		
A	256	273	335	353	390	478		

### ART. 894 - VERSIONE A "T"

	din	25	32	40	50	65	80	100
	L	58	61	60	73	81	89	152
	E	57	63	64	72	80,5	91	115
	A	262	271	275	334	355	397	477
	sms	25	38	51	63	76	101	
	L	58	60	73	81	89	160	
E	53	63,5	73	81	89,5	115		
A	256	273	335	355	390	477,5		

### ART. 896 - VERSIONE MANUALE A "L"

	sms	25	38	51	63	76		
	L	66,5	66,5	74	95	95		
	E	50,5	50	58,5	67,5	76		
	A	251	251	290	361	372		