

VALVOLE DI SICUREZZA
MATERIALE: AISI 304 - AISI 316L
P=PORTATA MAX (HL/ORA)
ART.1060 - VALV.DI SICUREZZA A SQUADRA DIN F/F

	DN	25	32	40	50	65	80	100
	A	52	58	65	78	95	110	130
	C	50	60	60	65	85		
	D	210	250	260	270	295		


ART.1062 - VALV.DI SICUREZZA A SQUADRA F/F GAS

	DN	1"	1 1/4	1 1/2	2"	2 1/2	3"	4"
	A	25	31	38	49	66	76	96
	C	50	65	70	70			
	D	210	250	260	270			

ART.1064 - VALV.DI SICUREZZA A SQUADRA M/M GAS

	DN	3/8	1/2"	3/4	1"			
	A	30	30	40	45			
	B	160	160	210	250			

ART.1066 - VALV.DI SICUREZZA "SV" MASCHIO GAS

	DN	1/4"	3/8	1/2"	3/4	1"	1 1/4	1 1/2
	A	50	50	50				
	B	25	25	25				
	DN	2"						
	A							
	B							

0-16 Bar

ART.1068 - VALV.DI SICUREZZA "ARAL" MASCHIO GAS*

	DN	1"						
	A	165						
	B	48						

0-13 Bar

ART.1070 - VALVOLA A DOPPIO EFFETTO DIN

	DN	25	32	40	50	65	80	100
	A	28	34	40	52	70	85	104
	B	74	78	82	86	90	110	140

ART.1072 - VALV.A DOPPIO EFFETTO A MORSETTO

	DN	40	50					
	A	33	49					
	B	65	76					
	C	147	170					

-20 +40 mBar

ART.1074 - VALV.A DOPPIO EFFETTO REGOLABILE

	DN	40	50					
	A							
	B							

-20 +300 mBar

ART.1076 - VALVOLA DI SFIATO A BAGNO D'OLIO

	DN	40	60	100				
	A	150	200	245				
	P	200	600	950				